



Ipcochemical Europe S.r.l.

Via Vailate, 79 – 26017 Pieranica (CR) – Tel:0373/71265- Fax: 0373/71465
P.IVA-C.F. IT03584730166 - ipcochemical@gruppoipcochemical.it
<http://www.ipcochemical-europe.com/>

ECO FLU

BROCHURE

DESCRIPTION

ECO FLU is a permanent type liquid antifreeze, monoethylene glycol-based, that contains inhibitors and anticorrosion compounds, totally nitrite-, amine- and phosphate-free; it is suitable to protect all metal parts of engine's cooling system.

AUTOMOTIVE PERFORMANCE LEVELS

ASTM D 3306

CUNA 956-16 [Gennaio 2012]

BS 6580

AFNOR NF R 15-601

APPLICATIONS

ECO FLU is recommended in cooling circuits of every type of vehicle engine;



it can be also used, if opportunely diluted, in industrial cooling plants



and fire-fighting systems.



PERFORMANCES

Corrosion protection towards all metals, particularly suitable for aluminum and its alloys.

Outstanding anti-oxidant e anti-encrusting characteristics, that ensure a perfect heat exchange, also with hard water.

High anti-foam capacity, thanks to a specific additive.

Long life protection, thanks to its high reserve alkalinity.

Fully compatible with seals and rubber or plastic components.

Protection against cavitation and consequent erosion risks.

Frost protection, at different concentrations in water, as shown in the following table:

ECO FLU %vol	20	30	35	40	50
WATER %vol	80	70	65	60	50
PROTECTION TEMPERATURE °C	-9	-17	-21	-25	-35

CUSTOM PACKAGES AVAILABLE

20 AND 25 LITERS CANISTER



200 LITERS DRUM



1000 LITERS CISTERN



TANK TRUCK

